



# Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 02/12/09

## DAP<sup>®</sup> 3.0<sup>™</sup> Advanced All-Purpose Sealant with Kwik Dry<sup>®</sup> Technology-White

- Caulk and expose to water after just 3 hours.
- Permanent waterproof seal.
- All-weather & sub-zero application.
- Indoor/outdoor use.
- Won't crack or shrink.
- Paintable.
- Lifetime guarantee.

**Packaging:** 9.0 fl. oz. (266 mL)  
**Color:** White  
**UPC Number:** 0 70798 18360 5

### Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Suite 200, Baltimore, Maryland 21224  
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.  
Order Information: 800-327-3339  
Fax Number: 410-534-2650  
Also, visit the DAP website at [www.dap.com](http://www.dap.com).

### Product Description:

DAP<sup>®</sup> 3.0<sup>™</sup> is an advanced, low-VOC all-purpose indoor/outdoor sealant formulated with Kwik Dry<sup>®</sup> Technology allowing it to be exposed to water and moisture after only three hours without washing out rather than the 24-36 hour waiting period other caulks and sealants may require. It can be applied in all weather and below freezing temperature applications. It will not crack or shrink, and it provides excellent adhesion, flexibility and durability for a permanent waterproof seal. Cured sealant is mold and mildew resistant. It is paintable, low odor and VOC compliant. Backed by a lifetime guarantee.

### Suggested Uses:

#### *Ideal for sealing around:*

- Window and door frames
- Moulding, trim and baseboards
- Siding
- Pipes
- Butt joints
- Corner joints
- Vents and ducts
- Other gaps and openings

**Adheres to:**

- Wood
- Aluminum
- Vinyl
- Plaster and drywall
- Painted surfaces
- Masonry, stone and brick
- Metal
- Glass
- Stucco
- Concrete

**Performance Characteristics:**

- Accelerated cure time allows exposure to water and moisture after only three hours without washing out.
- Provides a permanently waterproof seal.
- Cured sealant is mold and mildew resistant.
- Permanently flexible. Won't crack or shrink.
- Paintable with most acrylic latex paints. Use acrylic primer for oil-based paints.

**Surface Preparation & Application:**

1. Surface must be clean, dry and free of all old caulk, dirt, dust and grease.
2. Unscrew outer nozzle.
3. Cut inner nozzle at the thread point furthest away from the base of the nozzle.
4. Re-attach outer nozzle, and cut nozzle at a 45° angle to desired bead size.
5. Load cartridge into caulking gun.
6. Fill gap with sealant, pushing sealant ahead of nozzle.
7. If necessary, smooth bead with a finishing tool.
8. Allow sealant to cure for at least three hours before exposing to water. Sealant surface may still be tacky. Sealant reaches full cure in 24 hours.
9. Clean up excess uncured sealant from surface and tools with mineral spirits. Scrape or cut away excess cured sealant.
10. Paintable with most acrylic latex paints in 3 hours (surface may still be tacky). Use an acrylic primer for oil-based paints.
11. Store partially used cartridge in a cool dry place. Use the DAP CAP™ (purchased separately) to smooth, seal and finish caulk for professional results with no mess. Reseals cartridge for storage and reuse. When ready to use again, remove the cured material at the tip or cut the tip back. Use as soon as possible, preferably within a month.

***For Best Results:***

- Application temperature range is between -35°F and 140°F.
- Not recommended for continuous underwater use, on stovepipes or for surface defects.
- Store product below 80°F (27°C) away from extreme heat or moisture.
- Certain porous substrates such as concrete may require primer for best adhesion.

**Physical & Chemical Characteristics:**

Vehicle:	Advanced Polymer
Tooling Time:	20 minutes
Full Cure Time:	24 hours
Paintable:	Yes
Odor:	Very Mild
Consistency:	Smooth and Creamy
Filler:	Calcium Carbonate
Solids:	>99.9% by weight
Weight per Gallon:	12.5 ± 0.5 lbs/gallon
Elongation:	650 ± 50%

Tensile Strength: 170 ± 5 psi  
Elastic Modulus: 42 ± 5 psi  
Service Temperature Range (Cured sealant): -65°F to 200°F for continuous use, 250°F with excursions  
Application Temperature Range: -35°F to 140°F  
Freeze Thaw Stability: Passes 5 Cycles 0°F (1 cycle = 16 hrs. @ 0°F, 8 hrs. @ 70°F)  
Shelf Life: 12 months if unopened and stored in cool dry place  
Coverage: 49 linear feet at 3/16" diameter bead

MSDS No.: 000 10021 001

**Note:** The physical properties were tested under standard conditions of 23°C (73°F) at 50% relative humidity. Typical characteristic values should not be used as specifications.

**Clean Up:**

Before curing, remove excess material from surface and tools with mineral spirits. Clean hands with soap and water. After product has cured, excess material must be cut or scraped away.

**Safety:**

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSD sheet by visiting our website at [www.dap.com](http://www.dap.com) or by calling 888-DAP-TIPS.

**Lifetime Guarantee:**

DAP warrants the performance of this product for sealant purposes during the lifetime of your home. If not satisfied, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.